

24V Lead-Acid Battery Charger

Model No.		EA1050H	EA1050K	EA1050L	EA1050M	EA1050N	EA1065
Standard item							
INPUT	Input range	100 ~ 240VAC					
	Frequency	47 ~ 63Hz					
	Input current	1.8A Max					
	Inrush current	80.0Amps Maximum					
	Efficiency	80% TYP. At full load, Nominal Line					
	Hold Up Time	8.3ms Min					
	EMI/EMC	FCC part 15J class B, CISPER 22 class B					
OUTPUT	Over voltage protection	Auto Recovery					
	Short circuit protection	Auto Recovery					
	Leakage Current	0.75mA Max					
ENVIRONMENTAL	Operating temperature	0 ~ 40					
	Storage temperature	- 20 ~ 85					
	Storage humidity	5% ~ 95%					
CHARGE CURRENT		1.0A	1.2A	1.5A	1.8A	2.0A	2.0A
FAST CHARGE VOLTAGE		29.4V					
FLOATING CHARGE VOLTAGE		27.6V					
CASE SIZE (mm)		121x60x34.5					154x68.5x40.5
Weight		280g					380g

1. AC Inlet: IEC60320 C14
2. DC Cable & Plug: The standard DC cable is UL1185 18AWG 1200mm with plug 5.5x2.1x11mm, central positive or refer to the DC adapter plug appendix list.

EA1050



EA1065

